

The `afterpage` package*

David Carlisle
carlisle@cs.man.ac.uk

1995/10/27

This package implements a command, `\afterpage`, that causes the commands specified in its argument to be expanded after the current page is output.¹

1. Sometimes L^AT_EX's float positioning mechanism gets overloaded, and all floating `figures` and `tables` drift to the end of the document. One may flush out all the unprocessed floats by issuing a `\clearpage` command, but this has the effect of making the current page end prematurely. Now you can issue `\afterpage{\clearpage}` and the current page will be filled up with text as usual, but then a `\clearpage` command will flush out all the floats before the next text page begins.
2. An earlier mechanism to help with float placement was the optional argument `[H]` (meaning **HERE!**) which was originally added to the standard floating environments by `here.sty`, and is now provided by `float.sty`. However some `[H]` users have commented that they did not really mean 'Here!' They actually wanted 'Somewhere close'. This can now be achieved by `\afterpage{\clearpage\begin{figure}[H] ... \end{figure}}`. This ensures that the figure is at the top of the next page. (The `\clearpage` stops any other figures drifting past the `[H]` figure.)
3. Floating longtables. `longtable.sty` provides the `longtable` environment, a multi-page version of `tabular`. Many `longtable` users have told me that it is difficult to set the text surrounding the long table, and that they wanted a 'floating' version. As, presumably, `longtables` are long, they are probably too large to hold in memory, and float in the way that the `table` environment is floated, however if the table is in a separate file, say `ltfile.tex`, you can now use one of:
`\afterpage{\clearpage\input{ltfile}}`
`\afterpage{\clearpage\input{ltfile}\clearpage}`.
The first form lets text appear on the same page as the end of the longtable, the second ensures that the surrounding text starts again on a new page.

1 (*package)

`\afterpage` The token register used to save the old output routine.

2 `\newtoks\AP@output`

3 `\global\AP@output\expandafter{\the\output}`

A box register used to save any part of the next page which has already been processed.

4 `\newbox\AP@partial`

A box register used to save any footnote texts that are 'tied' to the text that gets saved in `\AP@partial`.

5 `\newbox\AP@footins`

*This file has version number v1.08, last revised 1995/10/27.

¹This is really a pre-release, to see whether people like the idea of a command like this. This implementation is *not* particularly robust. This implementation does not work in two column mode, and can get 'confused' by L^AT_EX's floating environments.

The following macro attempts to get safely into vertical mode, and then invokes a special output routine to grab the current page into `\AP@partial`.

```
6 \def\AP@savetop{%
```

Now begins a test to see what state we are in. `\AP@noindent` will be defined so as to return to this state (well, almost!) after afterpage has finished.

```
7 \ifvmode
```

Vertical mode. This is the simplest case, do nothing.

```
8 \let\AP@noindent\empty
9 \else\ifhmode
```

Horizontal mode. ‘Back out’ into vertical mode, removing the indentation box as we go. If in fact there was no indentation box, the output routine was invoked by `\noindent` (what bad luck!) so we have to remember to re-insert the `\noindent` before the paragraph is seen again. `\everypar` tokens have already been inserted, so don’t insert them again.

```
10 \setbox\z@\lastbox
11 \edef\AP@noindent
12 {{\everypar{}\ifvoid\z@\noindent\else\indent\fi}}%
13 \par
14 \else
```

The remaining (even worse) possibility that the output routine was triggered by the start of `displaymath` within a paragraph.

Come out of `displaymath` with `$$`, then adjust the spacing (getting into `vmode` at the same time). `\AP@noindent` will restart display math later. `\everydisplay` tokens have already been inserted (they apply to the math list that will be started by `\AP@noindent`, even though they were triggered by the display math that was closed by the lines below!). Save the values `\prevgraf` and `\predisplaysize` for use in the re-started math list.

```
15 \abovedisplayshortskip\z@\abovedisplayskip\z@
16 \belowdisplayshortskip\z@\belowdisplayskip\z@
17 \xdef\AP@disp{%
18 \predisplaysize\the\predisplaysize
19 \prevgraf\the\prevgraf\relax}%
20 $$\vskip-\baselineskip\vskip-\parskip
21 \edef\AP@noindent{%
```

Do not insert `\everydisplay` tokens again.

```
22 \toks@{\the\everydisplay}\everydisplay{}
```

Start `displaymath` mode with no spurious paragraph line above it. Restore `\prevgraf` and `\predisplaysize`. Use `\aftergroup` to restore the correct setting for `\everydisplay` after this display has finished.

```
23 {\everypar{}\noindent}$$\AP@disp\aftergroup\noexpand\AP@ed}%
24 \fi\fi
```

Now switch the output routine and remove everything from the current page into the box `\AP@partial`.

```
25 \begingroup
26 \nointerlineskip\null
27 \output{%
28 \global\setbox\AP@partial\vbox{%
29 \unvbox\@cclv
30 \global\setbox\@ne\lastbox}%
```

If the text that is saved in `\AP@partial` had footnotes, we’d better grab them as well otherwise they may come out on a page with the ‘afterpage’ text, before the page that has the footnote mark! (Added at v1.08.)

```
31 \global\setbox\AP@footins\box\footins}%
```

Having defined the output routine, trigger it...

```
32 \eject
33 \endgroup}
```

`\AP@` stores all the commands that must be executed after the page break.

```
34 \let\AP@\relax
```

Restore the `\everydisplay` register. `\ignorespaces` prevents a space or new-line after `$$` creating a rogue indentation or paragraph.

```
35 \def\AP@ed{\everydisplay\expandafter{\the\toks@}\ignorespaces}
```

Remove the current vertical list, insert the commands `\AP@` at the top of the page, and then re-insert the saved text.

```
36 \def\AP@@{%
37   \AP@savetop
38   \global\expandafter\let\expandafter\AP@\expandafter\relax\AP@
39   \par
```

The text originally at the top of this page is now stored in the box `\AP@partial`, including `\topskip` glue. Now we want to unbox `\AP@partial`, placing the baseline of the first row `\baselineskip` below the baseline of the last line coming from the afterpage text. If we assumed nothing has too much height or depth (and `\topskip` is rigid), it would be fairly trivial to position the contents of `\AP@partial` so that the baseline of the first row was `\baselineskip` below the last row just added.

In this version, I thought it might be fun to try to exactly achieve the `\baselineskip`-or-`\lineskip` calculation that \TeX normally does internally. The call to `\addboxcontents` does the right thing (I hope).

```
40   \addboxcontents\AP@partial
```

Now re-insert any footnote text. This may not be quite the right place, as the text that has just been unboxed may break over a page in its new position. Also it may not be the right number if the text from `\afterpage` itself contains footnotes. Too bad!

```
41   \ifvoid\AP@footins\else
42     \insert\footins{\unvbox\AP@footins}\fi
```

Now repair things if we started off in horizontal mode.

```
43   \AP@noindent}
```

If `\AP@` is not `\relax` then the current page already has some ‘afterpage’ commands, so just add the new commands to the end of the list. Otherwise save the commands in `\AP@`. (within a local group), and switch the output routine. (The new output routine just calls the old one if it is invoked by a \LaTeX float.

```
44 \long\def\afterpage#1{%
45   \ifx\AP@\relax
46     \gdef\AP@{{#1\par}}}%
47   \global\output{%
48     \the\AP@output
49     \ifnum\outputpenalty>-\@Mi
50       \global\output\expandafter{\the\AP@output}%
51       \aftergroup\AP@@
52     \fi}%
53   \else
54     \expandafter\gdef\expandafter\AP@\expandafter{\AP@{#1\par}}}%
55   \fi}
```

If we have got to the end of the document or `clearpage` just put the stuff out without any trickery.

```
56 \let\AP@clearpage\clearpage
57 \def\clearpage{%
58   \ifx\AP@\relax
59     \AP@clearpage
60   \else
61     \global\output\expandafter{\the\AP@output}%
62     \AP@clearpage
```

At this point (since v1.08) Need to clear `\AP@` *before* using its expansion, as otherwise hit an infinite loop. Sigh.

```

63   \global\expandafter\let\expandafter\AP@\expandafter\relax
64   \expandafter\expandafter\AP@
65   \fi}
66 \let\AP@endddocument\endddocument
67 \def\endddocument{%
68   \ifx\AP@\relax\else
69     \global\output\expandafter{\the\AP@output}%
70     \AP@clearpage
71     \global\expandafter\let\expandafter\AP@\expandafter\relax
72     \expandafter\expandafter\AP@
73   \fi
74   \AP@endddocument}

```

`\addboxcontents` Given a vbox #1, add to the current vertical list such that the end result is equivalent to the list that T_EX would have built had the contents of #1 (apart from any initial glue) been added individually to the current list.

So essentially, the problem is that of unboxing #1, but replacing the glue at the top of #1 with (something equivalent to) the `\baselineskip` or `\lineskip` glue that T_EX would normally have placed before the first box in #1. Also `\prevdepth` must be set at the end.

```
75 \def\addboxcontents#1{%
```

Perhaps I shouldnt use grouping here, as I probably don't really want to save #1. If it is removed, `\splittopskip` and `\splitmaxdepth` would need to be restored by hand.

First replace any glue at the top by `\vskip 0pt`.

```

76   \splittopskip\z@
77   \splitmaxdepth\maxdimen
78   \setbox#1\vbox{\break\unvbox#1}%
79   \setbox\z@\vsplit#1to\z@

```

Put the breakpoint back.

```
80   \setbox#1\vbox{\break\unvbox#1}%
```

Set `\skip@` to be height of #1 (without top glue)

```
81   \skip@\ht#1%
```

Now make the first baseline of the first row be `\vsize` from the top. (This assumes that the first row has height less than `\vsize`.)

```

82   \splittopskip\vsize
83   \setbox\z@\vsplit#1to\z@

```

Subtract the new height of #1 from `\skip@`, and add back on `\splittopskip`, so `\skip@` is now the height of the first row of #1 This may still be 0pt if (eg) a mark or whatsit is between the top glue and the first box. Save (this height – `\splittopskip`) in `\skip\tw@`.

```

84   \advance\skip@-\ht#1%
85   \skip\tw@\skip@
86   \advance\skip@\splittopskip

```

Now fake T_EX's `\baselineskip` calculation.

```

87   \advance\skip@\prevdepth
88   \advance\skip@-\baselineskip
89   \advance\skip\tw@\ifdim-\skip@<\lineskiplimit\lineskip\else-\skip@\fi

```

Finally add the glue.

```
90   \vskip\skip\tw@
```

Now unbox the box, setting `\prevdepth` by hand, as `\unvbox` (unlike `\box`) does not automatically set it.

```

91   \global\dimen@i\dp#1%
92   \unvbox#1}%
93   \prevdepth\dimen@i}

```

```
94 \endpackage
```